



SIP-T6680

SIP-T6680W

Main Features :

- 2.4-inch LCD display screen with backlight
- 2 SIP Account, 1*RJ9 headphone jack
- 2port 10/100M RJ45, PoE
- 2.4GHz & 5.8GHz Wireless (SIP-T6680W)
- Supporting Cloud
- Support Paging Call IP Speaker
- Power supply Adaptor DC5V / PoE
- Standalone Paging Call



TLS&SRTP OpenVPN



HD audio


Five-party
conference


DSS 2


Address
book

Descriptions :

SIP-T6680 Series is a feature-rich high-definition voice IP phone that supports 2 SIP accounts, 100M network ports, IPv6, and dual- network port PoE power supply. It has high-definition sound quality, unique appearance design, 17 languages display, added. Support 2.4GHz WIFI connection, compatible with mainstream IP PBX, changes multiple perspectives, and can access DSS user status keys. SIP-T6680 series can meet the needs of different user groups, provide strong guarantees for users with high product quality, and easily achieve high-quality communication.

Specification

Model	SIP-T6680 Series
Account	2*SIP accounts
Network Interface	2*10/100M adaptive Ethernet interface, with PoE power supply
Wireless Interface	2.4GHz & 5.8GHz WiFi connection for SIP-T6680W
Headphone	1*RJ9 headphone jack
Screen	2.4-inch black and white display with backlight
Power Supply	AC100-240V, output: DC 5V, IEEE 802.3af/at PoE
OS	Linux
Language	Support 17 languages (Simplified Chinese, Traditional Chinese, English, Turkish, Korean, Russian, French, Italian, German, Polish, Portuguese, Thai, Hindi, Arabic, Japanese, Spanish, Vietnamese)
Voice	High-definition voice, handle and hands-free mode support high-definition voice calls
Voice coding	G.711A/u, G.722, G.723 high/low, G.729 A/B, support DTMF in-band and out-of-band transmission (SIP INFO, DTMF Relay, RFC2833)
Protocol	Support SIP 1.0 (RFC2543), SIP 2.0 (RFC3261), IEEE 802.3/802.3 u 10 Base T/100Base TX, UDP / TCP/IP, TP, RTCP, SRTP, DHCP, PPPOE, DNS, Telnet, FTP, TFTP, HTTP, HTTPS, VAD/CNG, PPTP, L2TP, OpenVPN, SNTP, STUN
Functions	call hold, mute, transfer, call transfer (unconditional transfer, no answer transfer, busy transfer), multi-party conference, call waiting, personalized ringtones, address book import/download, automatic answer., it can store 500 phone numbers, 1000 call records, and 1200 all call records. support blacklist (optional); support encrypted call function.
Ringtone	10 ringtones can be selected (can be added at the factory if necessary).
Encryption	Support soft encryption such as AES, or hard encryption with encryption chip
Time	Support time setting (SNTP/SIP Server acquisition/manual)
Security	OpenVPN, TLS & SRTP encryption technology is integrated to ensure call security, so that every conversation is at ease.
Cartons Size	535×410×230 mm

Model	Network	PoE	DSS Expansion	Power Adapter
SIP-T6680	10/100M	√	X	Optional
SIP-T6680W	10/100M	√	X	Included