



Key Features:

- ※ 4*10/100Base-TX PoE ports, 2*10/100Base-T Uplink.
- ※ Protocol supports IEEE802.3af/at
- ※ PoE power budgeted 65Watt, each port 30Watt support
- ※ Supports up to 250m ultra-long distance transmission mode
- ※ Ports 1-4 support 10/100Mbps adaptive speed, ports 5-6 support 10/100Mbps adaptive speed
- ※ Plug-and-play, no configuration requirements
- ※ The metal casing and built-in power supply ensure excellent heat dissipation and long-term stable operation of the product.
- ※ AI (watchdog) function, restart automatically when crashed.

Product Parameters

Model	TCM-P4806F2	
Ethernet port Characteristic	Connector Type	1×4 RJ45, 1×2 RJ45
	Port Function	Power supply priority, fast transmission, MAC automatic learning and aging, IEEE802.3X full-duplex and back pressure half-duplex
	Transmission rate	10/100Mbps auto-negotiate ;
	Indicator Light	Each port has 1 Link/ACT 100Mbps and 1 power light; whole machine power indicator; extend indicator
	Transmission distance	10Base-T: ≤ 250m 100Base-TX: ≤ 100m
Exchange performance	Forward method	Store-and-forward
	MAC address table	1K
	Bandwidth	1.6G
Power parameters	Input voltage	100-240VAC
	Power consumption	Standby: ≤2W; whole: ≤65W
	PoE pin	1/2+,3/6-
	The port max rate	Port 1-3 max 30W , port 4 max 60W
Environment	Operating Temperature	-20℃ ~ 60℃
	Storage Temperature:	-30℃ ~ 70℃
	Operating Humidity	90% non-condensing
	Storage Humidity	95%, non-condensing
Physical properties	Size	180*100*34mm
	Weight	0.6kg