



Key Features:

- ※ Full Gigabit Power Link PoE Switch
- ※ 8*10/100/1000Base-TX PoE ports, 2*10/100/1000Base-T Uplink, auto negotiate.
- ※ Protocol supports IEEE802.3af/at
- ※ PoE power budgeted 120Watt, each port 30Watt support
- ※ Supports up to 250meters extend mode
- ※ Ports 1-8 support 10/100/1000Mbps, ports 9-10 support 10/100/1000Mbps, adaptive speed.
- ※ Plug-and-play design with easy operation and no configuration required
- ※ 6KV lightning protection function;
- ※ AI (watchdog) function, restart automatically when crashed.

Product Parameters

Model	TCM-P4810G4	
Port Characteristic	ConnectorType	8xRJ45, 1x2RJ45
	Transmission rate	10/100/1000Mbps auto-negotiate
	Port Function	Power supply priority, fast transmission, MAC automatic learning and aging, IEEE802.3Xfull-duplexand back pressure half-duplex
	Indicator Light	Each port has 1Link/ACT 100Mbps and 1power light; whole machine power indicator, VLAN indicator
	Transmission Speed	100BASE-T:14880pps/Port 1000BASE-TX:14800pps/Port
Exchange performance	Forward method	Store-and-forward (fullwire-speed)
	MAC addressable	2K
	Bandwidth	22G
Power parameters	Input voltage	AC100~240V
	Power consumption	Standby:≤3W;whole:≤120W
	PoE pin	1/2+,3/6-
	The port max rate	≤30W
Environment	Operating Temperature	-20℃ ~ 60℃
	Storage Temperature:	-30℃ ~ 70℃
	Operating Humidity	90% non-condensing
	Storagehumidity	95% non-condensing
Physical properties	Size	200*142*43mm
	Weight	1.05KG