



Key Features:

- ※ Hybrid Power Link PoE Switch
- ※ 16*10/100Base-TX PoE ports, 2*10/100/1000Base-T Uplink, 1xSFP Slot.
- ※ Protocol supports IEEE802.3af/at
- ※ PoE power budgeted 250Watt, each port 30Watt support
- ※ Supports up to 250m ultra-long distance transmission mode
- ※ Ports 1-16 support 10/100Mbps adaptive, ports 17-18 support 10/100/1000Mbps adaptive speed, port 19 SFP
- ※ All ports support line-speed forwarding for smoother transmission
- ※ Plug-and-play design with easy operation and no configuration required
- ※ 6KV lightning protection function;
- ※ AI (watchdog) function, restart automatically when crashed.

Product Parameters

Model	TCM-P4819G2S	
Ethernet port Characteristic	Connector Type	2×8 RJ45, 1×2 RJ45, 1x SFP
	Transmission rate	10/100Mbps auto-negotiate ; 10/100/1000Mbps auto-negotiate
	Transmission distance	10Base-T: ≤250m 100Base-TX: ≤100m 1000Base-T: ≤100m
Exchange performance	Forward method	Store-and-forward
	MAC address table	16K
	Bandwidth	10.8G
Power parameters	Input voltage	AC100~240V
	Power consumption	Standby: ≤30W; whole: ≤250W
	PoE pin	1/2+,3/6-
	The port max rate	≤30W
Environment	Operating Temperature	-20°C~60°C
	Storage Temperature:	-30°C to 70°C
	Operating Humidity	90% non-condensing
	Storage humidity	95% non-condensing
Physical properties	Size	312*185*46mm - 1U desktop or wallmount
	Weight	2.0Kg