


**Descriptions :**

The Network PA Horn speaker is a high-power speaker made of sturdy and virtually indestructible aluminum and iron alloy, offering maximum protection against shock and weather, making it ideal for installation in extreme conditions with an IP66 rating, whether in vehicles, boats, or outdoor installations. All are equipped with a sturdy and adjustable mounting bracket. This speaker is an active speaker, with a high-power class D amplifier built into it. Easy operation, configuration, operation, & remote monitoring.

**Features:**

- ※ Network 100BASE-TX,RJ-45 Connector
- ※ Protocol TCP/IP,Multicast,SIP,RTP, IGMP
- ※ Audio codec G.711a/u, G.722, G.729
- ※ Audio Decoding source MP3,WAV,WMA
- ※ RJ-45 Connector digital data audio input
- ※ Built-in of Class D amplifier Industrial grade
- ※ Speaker output 120W/150W
- ※ Power Source 220VAC 300W included
- ※ Ip66 Protection
- ※ Installation for indoor or Outdoor

**Spesification:**

| Model                 | TCM-H120SIP                                       | TCM-H150SIP          |
|-----------------------|---------------------------------------------------|----------------------|
| Rated Power           | 120Watt                                           | 150Watt              |
| Speaker drive         | 4 x 100W                                          | 4 x 100W             |
| Network               | 100BASE-TX,Auto MDI/MDI-X, RJ-45 connector        |                      |
| Network Protocol      | TCP/IP, UDP, SIP, Multicast, RTP, ARP, ICMP, IGMP |                      |
| Audio Codec           | G.711u,G.711a, G.722, G.729                       |                      |
| Audio Decoding Format | MP3,WMA,WAV                                       |                      |
| Audio bit rate        | 8 ~ 320Kbps                                       |                      |
| Frequency Responce    | 300Hz ~ 15KHz (±3dB)                              | 300Hz ~ 17KHz (±3dB) |
| Sound Pressure Level  | 134dB@1mtrs                                       | 136dB@1mtrs          |
| Amplifer Rated Output | 180W Class D                                      | 225W Class D         |
| Power Source          | Built-in, 220VAC 300Watt                          |                      |
| Broadcasting Mode     | Multicast & SIP Broadcasting Mode                 |                      |
| Dispersion angle      | H:110°                                            |                      |
| Dust/Water Protection | IP66                                              |                      |
| Operating Temperature | -30°C to +65°C                                    |                      |
| Operating Humidity    | 90% RH or less (no condensation)                  |                      |
| Finish                | Alluminium, Steel bracket                         |                      |
| Dimensions            | Ø485 x 505mm (±3mm)                               |                      |
| Weight                | 20.5Kg                                            |                      |