



Main Features:

- ※ Network 100BASE-TX, RJ-45 Connector
- ※ Protocol TCP/IP, Multicast, SIP, RTP, IGMP
- ※ Audio codec G.711a/u, G.722, G.729
- ※ Built-in of Class D amplifier 60W
- ※ Supresion Pressure Level (SPL) 105 max
- ※ Power 12V DC or PoE 90W (IEEE802.3bt)
- ※ Weatherproof for outdoor
- ※ Installation for indoor or outdoor

Descriptions:

Network PA Column Speakers can produce extraordinary sound for any outdoor or commercial application, these speakers can be mounted on walls or poles with an elegant shape. Outdoor installation applications with IP66 protection. These speakers are active speakers, inside which a class D power amplifier is installed with a 60Watt speaker load, the RJ45 input connector is equipped with PoE so there is no need to install a separate power supply cable. These speakers are very suitable for installation in areas for sound reproduction of announcements, emergency announcements, and playing background music such as shopping centers, restaurants, metro stations, hotels, coffee shops, school classrooms, etc. Integrated with audio broadcasting and PA software, making it very easy to distribute audio according to the target speaker. Easy operation, configuration & remote monitoring system.

Specification

Model	TCM-660CS/P
Rated Power	60Watt
Network	100BASE-TX,Auto MDI/MDI-X, RJ-45 connector
Network Protocol	TCP/IP, UDP, Multicast, SIP, RTP, IGMP
Audio Codec	G.711u, G.711a, G.722, G.729
Audio Format	MP3,WMA,WAV
Audio bit rate	8 ~ 320Kbps
Amplifier Rated Power	Built-in 60Watt internal Class D Power Amplifier
Audio Input	Data Rj45
Frequency Response	90Hz ~ 18KHz
SPL (1w/1m)	max 105dB
Speaker Driver	3"x1, 5"x2
Envirovement	Outdoor weatherproof IP66
Operating Temperature	-10°C ~ 55°C
Material	Aluminium
Finishing Color	White
Net Weight	5kg
Dimension	577x170x148mm