Model : TCM-ITC701A
TCM-ITC701V



Mini Network Audio Intercom



Mini Network Video Intercom

Features

- 2 SIP lines
- Built-in speaker and AEC algorithm
- Integrate smart security, audio intercom and broadcast
- With emergency call button interface, one-button call
- Support one output short circuit and one input short circuit for emergency button.
- Support PoE power supply
- Used in different environment and application scenarios .
- Water-proof, Dust-proof and Striking-proof design, avoiding malicious damage
- High compatibility Compatible with SIP-based mainstream IP PBX/softswitch/IMS platforms, such as Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya, etc .
- Supports ONVIF compliant IP cameras

Description

With 10/100M Ethernet interface, Mini Network Intercom is a wall-mounted 1 button help intercom terminal, which supports G.711,G.722, audio decoding. It receives audio data from SIP network, decodes and plays in real time, and also cofigures microphone input and speaker output. SIP intercom ,playback and other functions can be realized. As a terminal of SIP intercom system, it can be used in places where intercom, emergency alarm and radio call are needed, such as self-service banking, interrogation room, classroom, hospital, parking lot entrance and exit, etc. Mini Network Intercom terminal supports full-duplex two-way intercom and has good echo suppression. In addition, it supports standard SIP protocols and works well with standard SIP.

Specification

Model	TCM-ITC701A	TCM-ITC701V
Network	100BASE-TX,Auto MDI/MDI-X, RJ-45 connector	
Protocol	TCP/IP, UDP, Multicast, SIP, IGMP	
Audio Codec	G.711u, G.711a, G.722, G.729,Opus	
Audio	Built-in Microphone & Speaker , Full duplex voice	
Output	dry contact relay for emergency device	
Button	AutoDial 1 DSS Buttom	
Camera	N/A	HD Camera, H.264
	Support External ONVIF Camera	
Power Supply	PoE IEEE802.3af	
Broadcast mode	Direct call, Group Call, SIP Call	
Working Temp.	-40°C～ +70°C	
Working Humidity	95% RH or less (no condensation)	
Protection level	Ip66	
Shell material	Aluminum alloy shell, iron bottomshell	
Dimensions	85,5x85,5x52,5mm(WxHxL)	
Weight	0.85kg	

©2026TechmaTechnology-Spesifications are subject to change without prior notice