TCM-CX6000Pro

Multi-Site PAGA Central Manager



DESCRIPTION

The TCM-CX6000Pro provides centralized remote management and monitoring of multiple compatible PAGA servers across different sites. Each site server independently handles its local paging, background music (BGM), scheduling, and alarm functions, while the TCM-CX6000Pro enables a single operator to monitor and configure the managed sites through one interface.

KEY FEATURES

- Centralized management of up to 9 site servers (4 sites by default)
- Real-time device status monitoring
- Multi-site centralized device location and status monitoring
- Network connectivity over WAN, VPN, and private IP networks
- Multi-client user management

TECHNICAL SPECIFICATIONS

Item	Specification
Model	TCM-CX6000Pro
Product Type	Multi-Site PAGA Central Manager
Engine Architecture	Intel® Core™ Powered
Operating System	Linux
Network	1000BASE-TX, Auto MDI/MDI-X, RJ-45 Connector
Network Protocol	TCP/IP, HTTPS, REST API, WSS
Supported Server Platforms	TCM-BGM9000Pro, TCM-CX9800S
Site Management	Up to 9 site servers (4 by default)
Monitoring	Device Status Dashboard, E-Map
Configuration	Site Server Configuration
User Management	Multi-Client User Management
Operation Interface	Web-Based GUI (Browser)
Remote Call Station	Multi-Site Support
Working Temperature	-10 to +50°C
Working Humidity	10%–95%
Power Supply	AC 220–240V, 50/60Hz
Dimensions	482 × 67 × 250 mm (W × H × D)
Rackmount	19-inch, 1.5U
Weight	3.5 kg

Specifications are subject to change without notice.